



technical data

Supply voltage	220 - 240 V
Frequency	50/60 Hz
Maximum power consumption	3.7 kW
Maximum power rating	3.7 kW
Minimum fuse protection	1 x 16 A
Power levels	1 - 9, (switching of 2-ring/roaster)
Weight (incl. accessories/packaging)	7.4 kg
Surface material	SCHOTT CERAN®
Power supply cable	1.5 m (L, N, PE)
Dimensions (WxDxH)	327 x 515 x 75 mm
Cooking zone size	Ø 180 x 410 mm
Cooking zone power	3700 kW
Front cooking zone dimensions	Ø 180 mm
Front cooking zone power	1600 W
Number of cooking zone circuits front	1
Back cooking zone dimensions	Ø 120/180 mm
Back cooking zone power	600 W/1600 W
Number of cooking zone circuits rear	2

Product description

- Free choice of cooktop
- Oversized roaster
- Roaster switching
- 2-ring switching
- childproofing feature
- Cooking zone timers
- Timer
- Pause function
- Demo mode
- automatic heat up function

Scope of delivery

- HiLight glass ceramic cooktop CKCB
- glass ceramic scraper
- mounting straps
- height adjustment plate set

product- and planning instructions

- Ensure sufficient ventilation of the area below the cooktop.