



**technical data**

|                                      |                   |
|--------------------------------------|-------------------|
| Supply voltage                       | 220 - 240 V       |
| Frequency                            | 50/60 Hz          |
| Maximum power consumption            | 3.7 kW            |
| Maximum power rating                 | 3.7 kW            |
| Minimum fuse protection              | 1 x 16 A          |
| Power levels                         | 1 - 9, P          |
| Weight (incl. accessories/packaging) | 7.9 kg            |
| Surface material                     | SCHOTT CERAN®     |
| Power supply cable                   | 1.5 m (L, N, PE)  |
| Dimensions (WxDxH)                   | 327 x 515 x 58 mm |
| Front cooking zone dimensions        | 230 x 230 mm      |
| Front cooking zone power             | 2100 W            |
| Front cooking zone power setting     | 3700 W            |
| Back cooking zone dimensions         | 230 x 230 mm      |
| Back cooking zone power              | 2100 W            |
| Back cooking zone power setting      | 3700 W            |

**Product description**

- Oversized 4 24 cooking surface
- Oversized surface induction cooking zones
- Variable heat retention function
- childproofing feature
- bridging function
- Cooking zone timers
- Timer
- Pause function
- Demo mode
- automatic heat up function

**Scope of delivery**

- Surface induction glass ceramic cooktop CKFI
- glass ceramic scraper
- mounting straps
- height adjustment plate set

**product- and planning instructions**

- Please note that induction-compatible cookware must be used on induction cooktops
- Ensure sufficient ventilation of the area below the cooktop.