



**technical data**

Supply voltage	220 - 240 V
Frequency	50/60 Hz
Maximum power consumption	3.0 kW
Maximum power rating	3.0 kW
Minimum fuse protection	1 x 16 A
Power levels	1 - 9, P
Weight (incl. accessories/packaging)	9.8 kg
Surface material	SCHOTT CERAN®
Power supply cable	1.5 m (L, N, PE)
Dimensions (WxDxH)	327 x 515 x 116 mm
Cooking zone size	Ø 250 mm
Cooking zone power	2400 W
Cooking zone power setting	3000 W

**Product description**

- Variable heat retention function
- childproofing feature
- Cooking zone timers
- Timer
- Pause function
- Demo mode
- automatic heat up function
- pan size recognition
- residual heat display
- Increased resistance against breakage

**Scope of delivery**

- Induction glass ceramic wok CKIW
- glass ceramic scraper
- mounting straps
- height adjustment plate set

**Accessories**

- HIW1 BORA induction wok

**product- and planning instructions**

- As a result of the height of 116 mm, the device cannot be installed over the exhaust air
- Ensure sufficient ventilation of the area below the cooktop.
- Glass ceramic mould: Diameter 250 mm
- Use a wok that loses its magnetic properties when the temperature rises (overheating protection). We recommend the use of the wok available from us