



**technical data**

Supply voltage	220 - 240 V
Frequency	50/60 Hz
Maximum power consumption	5.0 kW
Maximum gas cooktop power	5.0 kW
Maximum power rating	20 W
Minimum fuse protection	1 x 0.5 A
Power levels	1 - 9, P
Weight (incl. accessories/packaging)	10.8 kg
Surface material	SCHOTT CERAN®
Power supply cable	1.5 m (L, N, PE)
Dimensions (WxDxH)	327 x 515 x 73 mm
high-power burner	800-3000 W
normal burner	550-2000 W
Front cooking zone dimensions	Ø 240 mm
Back cooking zone dimensions	Ø 200 mm

**product description**

- Compact size
- Minimalistic design
- Modular system
- Oversized 4 24 cooking surface
- Sunken gas burners
- Variable heat retention function
- Automatic reignition
- Dishwasher-safe pan supports
- automatic heat up function
- Demo mode

**scope of delivery**

- Gas glass ceramic cooktop CKG
- 2 x cast iron pan supports
- Gas nozzle set G20 / 20mbar natural gas (AT, BE, CH, CZ, DE, DK, ES, FI, FR, GB, GR, HU, IE, IT, LU, PT, SI, SK)
- Flexible gas connection tube, length 500 mm, 1/2" external thread
- glass ceramic scraper
- mounting straps
- height adjustment plate set

**accessories**

- BORA gas nozzle set natural gas G20/10 mbar PKGDS2010 (AUS, NZ)
- BORA gas nozzle set natural gas G20/13 mbar PKGDS2013 (RU)
- BORA gas nozzle set natural gas G20/20 mbar PKGDS2020 (AT, BE, CH, CZ, DE, DK, ES, FI, FR, GB, GR, HU, IE, IT, LU, PT, SI, SK)
- BORA gas nozzle set natural gas G25/20 mbar PKGDS2520 (DE, BE, FR)
- BORA gas nozzle set natural gas G20/25 mbar PKGDS2025 (BE, FR)
- BORA gas nozzle set natural gas G25/25 mbar PKGDS2525 (NL)
- BORA gas nozzle set liquid gas G30/G31 28-30 mbar PKGDS3028 (BE, CH, CZ, ES, FR, GB, GR, IE, IT, PT, SI, SK)
- BORA gas nozzle set liquid gas G30/G31 50 mbar PKGDS3050 (AT, DE)
- BORA burner set PKGBS
- BORA pan support small PKGTK
- BORA pan support large PKGTG

**Produkt- und Planungshinweise**

- Ensure sufficient air supply below the gas cooktop. Either over the front of the body (opening cross-section > 50 cm<sup>2</sup>) or over the plinth area (opening cross-section > 150 cm<sup>2</sup>)
- Provide a return flow aperture (opening cross-section > 1000 cm<sup>2</sup> per air cleaning unit) for recirculation in the plinth area
- Please note the local regulations and connection requirements applicable to gas cooktops
- Please take into account the special guidelines regarding the assembly and use of gas cooktop CKG (see operating and installation instructions)
- When operating a gas cooktop with a cooktop extractor, the gas flame can be affected (depending on the height of the power level on the cooktop extractor)